


S-Series 15" Panel PC (AMD Geode LX-800 500MHz CPU)

MODEL #: R15A83S-OFC3


Mechanical Design




Open Frame



Modularized Construction



- | | |
|--------------------------------|-------------------------------|
| 1. Brightness Adjustment Knodo | 8. RJ-45 |
| 2. USB(Optional) | 9. USB |
| 3. RS-232Conn.(Optional) | 10. CF Socket |
| 4. RS-232Conn.(Optional) | 11. VGA Conn |
| 5. Power/HD DLED | 12. RS-232Conn. |
| 6. Power On Button | 13. PS/2 |
| 7. Power Reset Button | 14. DC-IN Lockable Power Jack |



System Specifications

TFT Characteristics :

- Resolutions : 1024 x 768
- Brightness : 250 cd/m² (typ.)
- Contrast Ratio : 500 : 1 (typ.)
- Viewing Angles : -65~65(H); -55~65(V)
- Max Colors : 16.2M

SBC Specifications :

- Processor : AMD Geode LX-800 500MHz CPU
- BIOS : Award 4Mbit Flash
- System Chipset : AMD CS5536 Companion Device
- Memory Slot : 1 x SODIMM, Max 1GB DDR 400
- Graphic Chipset : AMD® Geode LX800 Integrated (64MB shared)
- IDE : 1 x IDE (UDMA 33)
- CF : 1 x Type I/II CF socket
- KB/Mouse : 1 x PS/2
- Ethernet : 1 x RJ-45 (Realtek RTL8110s 10/100 Mbps)
- VGA : 1 x VGA Conn.
- Audio : Built in AC97 codec
- USB : 4 x USB 2.0
- Serial : 3 x RS232, 1 x RS232/422/485
- Parallel : 1 x LPT
- Expansion Slot : 1 x MiniPCI
- Power Input : DC IN (Lockable, Power Jack)
- Certifications : CE, FCC, RoHS

Power Specifications :

- Power Input Temperature : DC IN (Lockable, Power Jack)
- Power Consumption : 12V, 32W (typ.)

Environment Considerations :

- Operating Temperature : 0 deg.C to 45deg.C
- Operating Humidity : 30% to 90% (non condensing)

Output Connectors :

- Ethernet LAN : 1 x RJ45-10/100Mbps
- Keyboard / Mouse : 1 x PS/2
- COM : 1 x RS232 9P DSUB(male)
- USB : 2 x USB Type-A Receptacle
- VGA Out : 1 x VGA 15P DSUB(female)
- CF : 1 x Type I/II Socket

Order Options :

SBC	PANEL PC
CPU : AMD LX-800 500MHz*	Mechanical : Open Frame
RAM : 256 MB DDR*	Panel Mount (5mm bezel)
512 MB DDR(Optional)	IP65 (10mm bezel)
1 GB DDR(Optional)	Chassis
Storage : 3.5" 80 GB HDD*	Touch : 5 Wires Resistive(Optional)
2.5" 40 GB HDD(Optional)	OS : Windows XPE(Optional)
* Default : 1 GB Compact Flash(Optional)	Windows XP (Optional)
	Linux(Optional)

Accessories :

- External Power Supply 80W w/power cord
- Y Cable for Keyboard / Mouse