



EC-type examination certificate

Registration number / Reference mark C3428NOIR/R3

This certificate replaces certificate C3428NOIR/R2.

The company

NoIR Laser Company, LLC

6155 Pontiac Trail
SOUTH LYON MI 48178
USA

Applicant's code NOIR

hereby receives the confirmation that the product/s

laser protection filter

of the type

IRD3 4base and 8base

conforms to

DIN EN 207:2010-04

**Essential Requirements according to
Annex II of Directive 89/686/EEC (Edition: 1989-12)**

Test report(s): 77369-PTB-02, 11434-PZA-05, 1030-PZA-07, 10625-PZA-10,
11471-PZA-10

Identification: Information see annex

This EC-type examination certificate is valid until 2015-10-18.


See annex for further information.

DIN CERTCO GmbH
Prüf- und Zertifizierungszentrum Aalen
Gartenstraße 133, 73430 Aalen



2010-10-19

Dipl.-Ing. Dipl.-Wi.-Ing. Sören Scholz
Notified Body 0196



Annex

to the Certificate with Registration No. C3428NOIR/R3, dated 2010-10-19

Herewith, DIN CERTCO PZA certifies that the model is in compliance with the basic requirements of the Directive 89/686/EEG for personal protective equipment. The certificate is based both / either on the tests and / or on the technical documentation submitted by the manufacturer.

Test report(s)

77369-PTB-02, 11434-PZA-05, 1030-PZA-07, 10625-PZA-10,
11471-PZA-10

Name and address of DIN CERTCO as the notified body - identification no. 0196 are to be indicated in the information brochure for the product.

This eye-protection is to be marked on the oculars and/or the frames. The marking must include:

Laser mode of operation	Spectral range in nm	Shade/ scale number	Identification
D,R	180 to 315	LB6+LB4	180-315 D LB6 + R LB4 NOIR CE
D,R	>315 to 400	LB4	>315-400 DR LB4 NOIR CE
D,I,R	700 to 770	LB1	700-770 DIR LB1 NOIR CE
D,I,R	>770 to 820	LB2	>770-820 DIR LB2 NOIR CE
D,I,R	>820 to 865	LB3	>820-865 DIR LB3 NOIR CE
D,I,R	>865 to 1400	LB4	>865-1400 DIR LB4 NOIR CE
D,I,R	940 to 1064	LB5	940-1064 DIR LB5 NOIR CE
M	940 to 1064	LB5	940-1064 M LB5 NOIR CE
M	>1064 to 1400	LB4	>1064-1400 M LB4 NOIR CE
D,I	>1400 to 1840	LB2	>1400-1840 DI LB2 NOIR CE
D,I	>1840 to 1950	LB1	>1840-1950 DI LB1 NOIR CE

Additional product specification